

Refracto – reliable refractive index wherever you need it

Refracto 30PX and Refracto 30GS are compact, easy-to-use refractometers for measurements in laboratory and production environments. Depending on the application, these instruments can be used in two ways: Either put it on a flat surface and place a drop of sample onto the measurement cell, or immerse the sensor directly into the fluid. As soon as you press the measurement key, the result is displayed in the desired units on the backlit LC-Display. You no longer need to rely on error-prone readings of dark/bright transitions as with optical instruments. Refracto even measures dark samples correctly. Because the refractive index is temperature dependent, Refracto also automatically compensates the result. The Refracto 30PX has a measuring cell made of optical glass, whereas the Refracto 30GS has a measuring cell made of sapphire. Sapphire has a higher refractive index and a better thermal conductivity than glass. For this reason the Refracto 30GS has an extended measuring range and registers the sample temperature more quickly.

PortableLab™ – Lab power in your hands!
Refracto is delivered in a special case which contains everything you need for successful measurements: Pipettes for sample handling, cleaning towels, flasks for samples and cleaning solutions, operating instructions and a CD-ROM with data transmission software, a tutorial to get started and more.



PortableLab™



Good-bye Abbé: Easy-to-perform refractive index measurements

A refractive index determination is the simplest way to quickly determine the quality of a substance. Using Refracto, the determination is faster and less prone to errors than traditional methods (e.g. Abbé-refractometer). Refracto can also store, print and transfer results to a PC.



Food:
Reliable quality control

Wherever syrup concentrates, saline solutions or vinegar are produced: Refractometers are essential tools for quality control. The refractive index helps you make sure everything has gone right in the production process. With Refracto, you can perform your quality checks directly in the production facility.



Grapes and fruit:
Direct display

With Refracto, you can not only display sugar content in Brix%, but also choose direct conversion into °Oechsle, T.A. 1990, °KMW, °Baume, HFCS42 and HFCS55, which are shown directly after the measurement.




Antifreeze:
Quick concentration determination

The measurement of the refractive index is the quickest and easiest method to check antifreeze concentration. Refracto will tell you within seconds whether the antifreeze contains the right amount of ethylene glycol, propylene glycol, ethanol or sodium chloride. It even allows you to directly read the freezing point of these fluids in °C or °F.



Soft drinks:
Simple sugar content determination

The precise measurement of the temperature during measurement and the automatic temperature compensation using built-in ICUMSA tables ensure highly reliable Brix% results.



Customized applications:
Your own calculations

With Refracto, any concentration measurement can be performed without manual calculation. Just define the corresponding formula and the instrument gives you the final result.

Refracto: Desktop features in a handheld instrument

Ease-of-use

The clearly labelled keyboard makes operation easy and efficient.

Temperature compensation

The refractive index of a sample depends on temperature. During measurement, Refracto determines the temperature and then corrects the refractive index to a standard temperature of 20 °C or any other temperature the user defines. To make quick measurements of different types of samples, you can easily switch between up to 10 user defined correction coefficients.

It is your choice: hand-held or bench-top

Refracto is a hand-held and a bench-top refractometer in one. You either place the instrument on a flat surface and add a drop of sample onto the measurement cell or immerse the cell directly into the sample.

Plain language interface


The backlit LC-Display of Refracto shows your results and settings in plain language. The simple and intuitive menu structure allows you to change the settings within seconds. You hardly need an instruction manual.

Measurement cell with temperature sensor

Refracto determines refractive index using the total reflection method. The glass prism of the measurement cell of the Refracto 30PX (right) is held by a stainless steel ring, whereas the prism of the Refracto 30GS (left) is made of sapphire, the ring of hard gold plated brass. Sapphire has a higher refractive index and a better thermal conductivity than glass. For this reason the Refracto 30GS has an extended measuring range and registers the sample temperature more quickly.

Save and transfer your data whenever you want

Refracto stores up to 1100 results including sample identification, measurement unit, temperature compensation coefficient, date and time. You are free to transfer the data (together with an instrument identification) to a PC or printer any time using the infrared interface. The PC software to do this comes with Refracto.



Mettler-Toledo GmbH Analytical,
CH-8603 Schwerzenbach, Switzerland
Phone +41-1-806 77 11,
Fax +41-1-806 73 50
Internet; <http://www.mt.com>

- AT** Mettler-Toledo Ges.m.b.H., A-1100 Wien
Tel. +43-1-604 19 80, Fax +43-1-604 28 80
- AU** Mettler-Toledo Ltd., Port Melbourne, 3207 Victoria
Tel. +61-1-300 659 791, Fax +61-3-9645 3935
- BE** N.V. Mettler-Toledo S.A., B-1932 Zaventem
Tel. +32-2-334 02 11, Fax +32-2-334 03 34
- CA** Mettler-Toledo, Inc., Mississauga, Ontario L4V 1J2
Tel. +1-800-638 8537, Fax +1-905 612 8094
- CH** Mettler-Toledo (Schweiz) AG, CH-8606 Greifensee
Tel. +41-1-944 45 45, Fax +41-1-944 45 10
- CN** Mettler-Toledo (Shanghai) Ltd., Shanghai 200233
Tel. +86-21-6485 0435, Fax +86-21-6485 3351
- CZ** Mettler-Toledo, s.r.o., CZ-10000 Praha 10
Tel. +420-2-72 123 150, Fax +420-2-72 123 170
- DE** Mettler-Toledo GmbH, D-35353 Giessen 11
Tel. +49-6-41 50 70, Fax +49-6-41 507 319
- DK** Mettler-Toledo A/S, DK-2600 Glostrup
Tel. +45-4327 0800, Fax +45-4327 0828
- ES** Mettler-Toledo S.A.E., E-08908 L'Hospitalet del Llobregat
Tel. +34-93-223 76 00, Fax +34-93-223 76 01
- FR** Mettler-Toledo s.a., F-78222 Viroflay Cedex
Tel. +33-1-3097 1717, Fax +33-1-3097 1773
- HK** Mettler-Toledo HK Ltd., Cheun Sha Won Kowloon
Tel. +852-2744 1221, Fax +852-2744 6878
- HR** Mettler-Toledo, d.o.o., HR-10000 Zagreb
Tel. +385-1-292 06 33, Fax +385-1-295 81 40
- HU** Mettler-Toledo, Kft, H-1139 Budapest
Tel. +36-1-288 40 40, Fax +36-1-288 40 50
- IN** Mettler-Toledo India Pvt. Ltd, 400 072 Mumbai
Tel. +91-22-285 708 08, Fax +91-22-285 750 71
- IT** Mettler-Toledo S.p.A., I-20026 Novate Milanese
Tel. +39-2-333 321, Fax +39-2-356 29 73
- KZ** Mettler-Toledo C.A. 480009 Almaty
Tel. +7-3272-980 834, Fax +7-3272-980 835
- MY** Mettler-Toledo (M) Sdn. Bhd. 40150 Shah Alam
Tel. +60-3-7845 5773, Fax +60-3-7845 8773
- MX** Mettler-Toledo S.A. de C.V., México C.P. 06430
Tel. +52-55-554 75700, Fax +52-55 554 12366
- NL** Mettler-Toledo B.V., NL-4004 HA Tiel
Tel. +31-344 63 8363, Fax +31-344 63 8390
- PL** Mettler-Toledo, Sp. z o.o., PL-02-924 Warszawa
Tel. +48-22-651 92 32, Fax +48-22-651 71 72
- RU** Mettler-Toledo C.I.S., 101000 Moscow
Tel. +7-095-921 92 11, Fax +7-095-921 63 53
- SE** Mettler-Toledo AB, S-12008 Stockholm
Tel. +46-8-702 50 00, Fax +46-8-642 45 62
- SG** Mettler-Toledo (S) Pte. Ltd., 139959 Singapore
Tel. +65-689 000 11, Fax +65-689 000 12
- SK** Mettler-Toledo s.r.o., SK-82 104 Bratislava
Tel. +421-43 42 74 96, Fax +421-43 33 7 190
- SI** Mettler-Toledo, d.o.o., SI-1236 Trzin
Tel. +386-1-562 18 01, Fax +386-1-562 17 89
- TH** Mettler-Toledo (Thailand), Huy Kwang Bangkok 10310
Tel. +66-2-723 0300, Fax +66-2-719 6479
- UK** Mettler-Toledo Ltd., Leicester, LE4 1AW
Tel. +44-116-235 70 70, Fax +44-116-236 63 99
- US** Mettler-Toledo, Inc., Columbus, OH 43240-2020
Tel. +1-614-438 4511, Fax +1-614-438 4900
- L.A.** Mettler-Toledo, Latin America, Miami, FL 33122-1528
Tel. +1-305-351 2442, Fax +1-305-351 2425

PortableLab™

Refracto 30GS
portable high-end refractometer

Refracto 30PX
portable refractometer

Densito 30PX
portable density meter

X-mate^{Pro}
portable pH/multiparameter-instrument

Refracto 30PX / 30GS Refractometer



PortableLab™

Specifications Refracto 30PX / Refracto 30GS

Measurement method: Determination of the angle of total reflection of the D-line of sodium (589.3 nm) • **Refractive index:** Measurement range: 1.32 – 1.50 (PX), 1.32 – 1.65 (GS), Resolution: 0.0001, Accuracy: ± 0.0005 • **Brix%:** Measurement range 0 – 85 Brix%, Resolution: 0.1 Brix%, Accuracy ± 0.2 Brix% • **Temperature:** Measurement range: 10 – 40 °C, Resolution: 0.1 °C, Display: °C or °F, Ambient temperature: 5 – 35 °C • **Units of measurement:** nD, nD temperature compensated, Brix%, HFCS42, HFCS55, T.A. 1990, °KMW (Babo), °Baume, °Oechsle (D, CH), w/w%, v/v%, spec. gravity and freezing point (°C or °F) for ethanol and NaCl, w/w%, v/v% and freezing point (°C or °F) for ethylene glycol and propylene glycol, w/w% and v/v% for isopropanol, user defined unit • **Temperature compensation:** With user-defined temperature compensation coefficient (nD temperature compensated, user defined), or automatically (all other units). Up to 10 temperature correction coefficients can be stored in the instrument • **Calibration:** With pure water • **Data memory:** For up to 1100 results (result with unit, sample identification, temperature correction coefficient, date and time) • **Display:** Backlit LC-Display • **Interface:** Infrared for data transfer to PC and printer (IrDA or RS232C) • **Weight:** Approx. 250 g • **Batteries:** 2 x LR3, 1.5 V, type AAA approx. 60 hours battery life (one measurement per minute) • **Materials:** Housing: PBT. Measurement cell (PX): Glass, stainless steel. Materials with sample contact (PX): Glass, stainless steel, PBT. Measurement cell (GS): Sapphire, hard gold plated brass. Materials with sample contact (GS): Sapphire, gold, PBT.

Subject to technical changes.
© 06/2003 Mettler-Toledo GmbH
Printed in Switzerland 51724227A

PortableLab™

METTLER TOLEDO